

**AN ORDINANCE
OF THE
CITY OF MINNEAPOLIS**

By Palmisano

Amending Title 20, Chapter 535 of the Minneapolis Code of Ordinances relating to Zoning Code: Regulations of General Applicability.

The City Council of the City of Minneapolis do ordain as follows:

Section 1. That section 535.90 be amended to read as follows:

535.90. ~~Minimum size and width, principal entrance and windows, and location of attached garage requirements~~ General standards for residential uses.

(a) *Size and width.* The minimum gross floor area of a dwelling unit, except efficiency units, shall be five hundred (500) square feet. The minimum gross floor area of efficiency units shall be three hundred fifty (350) square feet. Not less than eighty (80) percent of the habitable floor area of single or two-family dwellings and multiple-family dwellings of three (3) and four (4) units shall have a minimum width of ~~twenty-two (22)~~ twenty (20) feet.

(b) *Principal entrance.* Single and two-family dwellings and multiple-family dwellings of three (3) and four (4) units shall include a principal entrance facing the front lot line. Subject to Table 535-1, Permitted Obstructions in Required Yards, the principal entrance shall be connected to the public sidewalk by an ~~impervious~~ hard-surfaced walkway not less than three (3) feet wide and shall include stairs where needed. Where no public sidewalk exists, the walkway shall extend to the public street. The principal entrance may face a side lot line when part of a front vestibule or extended portion of the front façade, provided the entrance is located no further than eight (8) feet from the façade closest to the street.

(c) *Windows.* Not less than fifteen (15) percent of the walls on each floor of single and two-family dwellings and multiple-family dwellings of three (3) and four (4) units that face a public street shall be windows. Not less than five (5) percent of the walls on each floor of single and two-family dwellings and multiple-family dwellings of three (3) and four (4) units that face a rear or interior side lot line shall be windows. Half stories shall not be subject to the minimum window requirement.

(d) *Attached garage facing the front lot line.* Attached accessory uses designed or intended for the parking of vehicles accessory to single and two-family dwellings and multiple-family dwellings of three (3) and four (4) units shall extend no more than five (5) feet closer to the front lot line than the façade of a habitable portion of the first story of the dwelling when the garage door or doors face the front lot line. In addition, the width of the garage wall facing the front lot line, including basement-level garages, shall not exceed sixty (60) percent of the width of the entire structure.

Section 2. That section 535.280 be amended to read as follows:

535.280. Obstructions in required yards. (a) *In general.* All required yards shall remain open and unobstructed from ground level to the sky, except as otherwise provided below.

(b) *Permitted obstructions.* Accessory uses and structures and projections of the principal structure may be located in a required yard only as indicated by a "P" for permitted in Table 535-1 Permitted Obstructions in Required Yards.

(c) *Additional limitations.* In no case shall any permitted obstruction be located closer than one (1) foot from the property line, except for driveways, walkways, fences, detached accessory buildings, the storage of firewood and containers for the removal of household refuse, subject to the provisions of this section. In addition, notwithstanding Table 535-1 Permitted Obstructions in Required Yards, required interior side yards for nonresidential uses shall remain unobstructed from the ground level to the sky, except that fencing and retaining walls shall be allowed.

(d) *Interior side yards for detached buildings accessory to dwellings.* The interior side yard requirement for a detached accessory building may be reduced to one (1) foot when the entire accessory building is located in the rear forty (40) feet or rear twenty (20) percent of the lot, whichever is greater, provided that the accessory building shall be located not less than ten (10) feet from any habitable portion of a principal structure on the adjoining lot ~~has its rear wall at least forty (40) feet from the rear lot line.~~ Further, the required side yard for a detached accessory building may be eliminated where adjoining property owners construct detached garages sharing a common wall and which are located in the rear forty (40) feet. Where the interior side yard is reduced, eaves, including gutters, shall not be less than six (6) inches from the property line, except where a common wall is allowed.

(e) *Rear yards for detached buildings accessory to dwellings.* The rear yard requirement for a detached accessory building may be reduced to one (1) foot, except where vehicle access doors face the rear lot line, in which case no reduction of the required yard is permitted. Further, where a rear yard abuts a required side yard no reduction of the required yard is permitted unless the entire accessory building is located in the rear forty (40) feet or rear twenty (20) percent of the lot, whichever is greater, and is located behind the rear wall of the principal structure on the adjacent property to the rear. The required yard along such adjacent property may be eliminated where adjoining property owners construct detached garages sharing a common wall and which are located in the rear forty (40) feet of both properties. Where the rear yard is reduced, eaves, including gutters, shall not be less than six (6) inches from the property line, except where a common wall is allowed.

(f) *Accessory buildings on reverse corner lots.* An accessory building shall be no closer to the side lot line adjacent to the street than a distance equal to two-thirds of the depth of the required front yard specified in the yard requirements table of the district of the

adjacent property to the rear. Further, an accessory building shall not be located within five (5) feet of a rear lot line that coincides with the side lot line of a property in a residence or office residence district. However, where the entire accessory building is located in the rear forty (40) feet or rear twenty (20) percent of the lot, whichever is greater, and is located ~~behind the rear wall of the~~ not less than ten (10) feet from any habitable portion of a principal dwelling on the adjacent property, only one (1) foot shall be required along such adjacent property line, except as otherwise prohibited by this zoning ordinance. Further, the required yard along such adjacent property may be eliminated where adjoining property owners construct detached garages sharing a common wall and which are located in the rear forty (40) feet.

(g) *Interior side yards for driveways accessory to dwellings.* The yard requirement for a driveway may be eliminated where adjoining property owners share a common driveway.

(h) *Rear yards.* For purposes of Table 535-1 Permitted Obstructions in Required Yards, a rear yard abutting a required side yard shall be considered an interior side yard and shall be subject to the permitted obstructions regulations for such interior side yard.

Section 3. That Table 535-1 of the above-entitled ordinance be amended to read as follows:

Table 535-1 Permitted Obstructions in Required Yards

<i>Type of Obstruction</i>	<i>Front or Corner Side Yard</i>	<i>Interior Side Yard</i>	<i>Rear Yard</i>
Balconies, decks and ground level patios not exceeding fifty (50) square feet in area and projecting not more than four (4) feet into the required yard. Such balcony, deck or ground level patio may project into a required interior side yard of a multiple family dwelling of four (4) or more stories, provided such balcony, deck or ground level patio shall be located no closer than ten (10) feet from the interior side lot line. <u>Ground-level patios up to one hundred (100) square feet, constructed of decorative concrete, pavers or stone, may extend more than four (4) feet into the required front yard accessory to single- and two-family dwellings and multiple-family dwellings having three (3) or four (4) dwelling units provided the patio is located not less than ten (10) feet from a public sidewalk and shall be designed in a manner that would prevent the patio from being used for off-street parking.</u>	P		P

Section 4. That Chapter 535 of the Minneapolis Code of Ordinances be amended by adding thereto a new Section 535.315, to Article IV, Protection of Natural Features, to read as follows:

535.315. Groundwater management. All development shall comply with all applicable regulations governing groundwater. Single and two-family dwellings shall be designed and constructed in a manner that does not rely on permanent groundwater discharge. The building official may request evidence, including soil testing, demonstrating that development will not extend into groundwater resources and may deny any application for a permit where an applicant has failed to demonstrate that subsurface development would maintain a sufficient separation from groundwater.