

2014-Or-____

**AN ORDINANCE
of the
CITY OF
MINNEAPOLIS**

By: A. Johnson

Amending Title 10, Chapter 188 of the Minneapolis Code of Ordinances relating to Food Code: Administration and Licensing.

The City Council of The City of Minneapolis do ordain as follows:

That Section 188.450 of the above-entitled ordinance be and is hereby repealed:

~~**188.450. Toilet facilities required.** Each food establishment shall provide water flush toilet facilities that are completely enclosed and which are connected to a sewerage system for use of its employees. Separate toilets must be furnished for each sex when five (5) or more employees of opposite sex are on duty at any one time. In every new or remodeled toilet room mechanical ventilation must be installed and used in a manner as to provide at least ten (10) changes of air per hour. Toilet seats and fixtures shall be of sanitary design, shall be kept clean and in good repair. The doors of all toilet rooms shall be self-closing. If vestibules are provided, they must be well lighted and kept clean. When toilet facilities are provided for patrons, such facilities shall meet the requirements of this section. Hand washing signs shall be posted in the employees' toilet room, directing them to wash their hands before returning to work. Conveniently located toilet facilities must be provided for patrons of all food establishments which sell hot drinks and other prepared hot foods for consumption on the premises.~~

2014-Or-____

**AN ORDINANCE
of the
CITY OF
MINNEAPOLIS**

By: A. Johnson

Amending Title 14, Chapter 364 of the Minneapolis Code of Ordinances relating to Liquor and Beer: Liquor Regulations.

The City Council of The City of Minneapolis do ordain as follows:

That Section 364.110 of the above-entitled ordinance be amended to read as follows:

364.110. Restroom facilities required. In each establishment wherein liquor or beer is sold pursuant to an "on sale" license, there shall be installed and maintained proper restroom facilities which comply with all requirements of any applicable code, statute, rule or regulation ~~at least one toilet room for each sex. In each toilet room for use by women there shall be installed and maintained at least one water closet and one lavatory. In each toilet room for use by men there shall be installed and maintained at least one water closet, one lavatory, one urinal and a properly installed and maintained floor drain sufficient at all times to keep such floor dry and in a sanitary condition. All water closet bowls shall be of extended lip pattern styles equipped with an open front without covers, and shall at all times be kept clean, sanitary and in good working condition. The floors and side walls, except doors, to a height of at least three (3) feet above the floor, of all toilet rooms and urinal compartments shall be constructed of noncorrosive and nonabsorbent materials, and approved by the director of inspections. Whenever possible, toilet rooms shall not be installed in cellars or basements, but when necessary, toilets may be located in a basement. When all toilet rooms are on the same floor, the entrances thereto shall be located as far apart as practicable, and each shall be plainly marked to indicate whether for men or women. Stairways to basement toilets shall be at least thirty (30) inches wide and of safe and substantial construction and with sufficient headroom. An iron pipe or other suitable handrail or guide shall be installed for the full length of such stairway, and the same shall be well lighted at all times.~~

2014-Or-___

**AN ORDINANCE
of the
CITY OF
MINNEAPOLIS**

By: A. Johnson

Amending Title 14, Chapter 368 of the Minneapolis Code of Ordinances relating to Liquor and Beer: Beer Regulations.

The City Council of The City of Minneapolis do ordain as follows:

That Section 368.90 of the above-entitled ordinance be and is hereby repealed:

~~**368.90. Restroom facilities.** In each tavern where beer is sold pursuant to an on-sale beer license there shall be installed and maintained for the public use at least one toilet room for each sex. In each restaurant where beer is sold pursuant to an "on sale" license, where the room or rooms in which meals or beverages are sold occupy or have a floor area of more than six hundred (600) square feet inclusive of the space occupied by or used for counters, fountains, iceboxes, coolers, bars or toilet facilities, there shall be installed and maintained for the public use at least one toilet room for each sex, except businesses catering only to men, and in each such restaurant where the room or rooms in which meals or beverages are served occupy or have a floor area of less than six hundred (600) square feet including the space occupied by or used for counters, fountains, iceboxes, coolers, bars or toilet facilities, there shall be installed and maintained for public use at least one toilet room. Where but one toilet room is required, it shall be equipped with at least one water closet, one lavatory and a properly installed and constructed floor drain sufficient at all times to keep the floor thereof dry and in a sanitary condition. In each toilet room for use by women there shall be installed and maintained at least one water closet and one lavatory. In each toilet room for use by men there shall be installed and maintained at least one water closet, one lavatory, one urinal and a properly installed and maintained floor drain sufficient at all times to keep such floor dry and in a sanitary condition. All water closet bowls shall be of extended lip pattern style and equipped with an open-front seat without covers, and shall at all times be kept clean, sanitary and in good working condition. The floor and side walls (except doors) to a height of at least three (3) feet above the floor, of all toilet rooms and urinal compartments shall be constructed of noncorrosive and nonabsorbent materials and approved by the director of inspections. Whenever possible, toilet rooms shall not be installed in cellars or basements, but when necessary, toilets may be located in a basement. When all toilet rooms are on the same floor, the entrances thereto shall be located as far apart as practicable, and each shall be plainly marked to~~

indicate whether for men or women. Stairways to basement toilets shall be at least thirty (30) inches wide and of safe and substantial construction and with sufficient headroom. An iron pipe or other suitable handrail or guide shall be installed for the full length of such stairway, and the same shall be well lighted at all times.