

DOCUMENT 00 91 13

ADDENDUM 2

BOSSEN FIELD PARK SITEWORK IMPROVEMENTS
PROJECT NO. 193803068
MINNEAPOLIS, MINNESOTA

March 22, 2016

Number of Pages: 2 (includes this sheet)

To: All Planholders of Record via Quest CDN

From: Stantec
2335 Highway 36 West
St. Paul, Minnesota 55113
(651) 636-4600 – General Office
(651) 604-4861 – Stuart Krahn, Project Manager

The following changes, additions, and deletions are hereby made a part of the Bidding Documents. Bidder shall acknowledge receipt of this Addendum on the Bid Form. Failure to do so may result in rejection of the Bid.

SECTION 01 00 10 – SUMMARY OF WORK

- 1. Add the following to Paragraph 05 USE OF THE SITE:

The Notice to Proceed is anticipated in mid-May, 2016. The Contractor will have immediate access to the southern portion of the site (Fields 6 and 7). The northern portion of the site that includes fields 2, 3, 4, and 5 is required to stay available for ongoing use by the City of Minneapolis softball programs until August 8, 2016.

SECTION 26 05 33 – RACEWAYS BOXES FOR ELECTRICAL SYSTEMS

- 2. Replace paragraph 3.02.N with the following:
 - a. Contractor shall install conduit by trenching, plowing, or directional drilling.
 - i. Trenching for underground conduit with a minimum size trench. 3 inches of sand shall be placed below and above buried conduit in trench. All fill material shall be placed in 12-inch lifts and compacted to 90-Percent Standard Proctor Density. Underground warning tape shall be laid in the trench approximately 9 inches below the surface. Excavating, backfilling, and grading shall comply with Division 31.
 - ii. Conduit shall be directional drilled under existing sidewalks, parking lots, and entrance drives.

SECTION 31 23 00 – EXCAVATION AND FILL

- 3. Add new Paragraph 2.01.D which reads as follows:
 - a. Ballfield Aggregate: Clean ballfield aggregate shall be salvaged from the existing infield areas and reused as the bottom layer of ballfield aggregate under new aglime areas. New ballfield aggregate shall be 100 percent Bryan Red Rock athletic field crushed red dolomitic limestone (Red Ball Diamond Rock), obtained from Bryan Rock Products of Shakopee, MN, Phone (952) 445-3900. No substitutions will be allowed for this product. Product gradation shall conform to the following requirements:

3/8 inch sieve	100 percent passing
#4 sieve	95 percent to 100 percent passing
#40 sieve	35 percent to 50 percent passing
#80 sieve	25 percent to 35 percent passing
#200 sieve	15 percent to 25 percent passing

- 4. Add new Paragraph 2.01.E which reads as follows:
 - a. ¾" Minus Crushed Bryan Red Rock: As shown on Drawing C1.01N, this material shall consist of ½" or ¾" Bryan Red Rock with fines to create a compacted, walkable, non-muddy surface over the area where the future concessions/restroom building is located. The Weed Inhibiting Fabric shall conform to MnDOT Spec. 3733, Type 1. Geotextile shall not be left exposed to the sun for a period in excess of 7 days without being covered.

LIST OF ATTACHMENTS

None

END OF DOCUMENT